

tesa® 53123 PV18 General Purpose Masking Tape

tesa® 53123 is a cremed colored universal use paper masking tape suited for various non-critical applications. It is frequently used for masking indoors, light duty spray painting, bundling, fixation, packaging and label.

Features & Benefits:

- Tear resistant backing provides demasking in one piece
- Excellent adherence of paints and fillers
- Good peel adhesion provides secure bond on different substrates
- Residue free removal up to 3 days indoor
- Temperature resistance up to 60°C / 1 h and 80°C / 0,5h
- Consistent tesa Quality

Main Application

- Indoor masking
- Light duty spray painting
- Bundling, fixation, packaging and labelling

Technical Data

| | | | |
|---------------------|-----------------------|--------------------------|---------|
| ▪ Backing material | slightly-creped paper | ▪ Elongation at break | 10 % |
| ▪ Total thickness | 135 µm | ▪ Tensile strength | 27 N/cm |
| ▪ Type of adhesive | natural rubber | ▪ Temperature resistance | 60 °C |
| ▪ Adhesion to steel | 2.6 N/cm | | |

Properties

| | | | |
|--------------------|------|---------------------|-----|
| ▪ Hand tearability | ●●●● | ▪ Sharp colour edge | ●●● |
| ▪ Easy to remove | yes | ▪ Conformability | ●●● |
| ▪ Paint anchorage | ●●●● | | |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=53123>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.